



Features

- 500 VA control transformer. Protected with thermomagnetic circuit breakers
- Protection against loss of ground wire, instantaneous trip
- Voltage presence indicator, detection range 30 to 600 VAC.
- Disconnect contactor 150, 265, 400 AMP. Control 120 VAC.
- Dehumidifying resistor
- Control wiring harness
- Control wiring made with harnesses
- Door locking with screw clamps
- Interchangeable connection provided

Features

System	3 phases 4 wire
Voltage	440 - 480 VCA
Capacity	150, 250 o 400 AMP
Control voltage	120 VCA
Ground fault disconnection time	From 30 a 2000mS
Power outlet and receptacle	Model DR metric capacity 150, 250 AMP (150 or 250 ampere models only)
Enclosure	Metal NEMA 4, gray ANSI 61
Indicator lights	22 MM metallic LED type, NEMA 4
Buttons	22 MM metallic LED type, NEMA 4
Actuating lever	Industrial use with locking device and padlock holder



Suggested spare parts

Code	Description
GM 200	Protection relay for ground wire loss
HARNESS GM200 KIT	GM200 plug and play harness
HARNESS 250 KIT	Full control harness
16301-3	Connection terminals for voltage supply voltage

Ordering information		Degree of protection	Material and finish	Receptaculum	Approx weight	Dimensions
MPCENT48015014E	Standard Sentinel 50 A 480 includes outlet and handle	NEMA 4	A36 steel / Polyester	Meltric 150	154.32 lbs	36" X 30" X 12"
MPCENT48025014E	Standard Sentinel 250 A 480. includes outlet and handle	NEMA 4	A36 steel / Polyester	Meltric 250 A	165.34 lbs	36" X 30" X 12"
MPCENT48040014E	Standard Sentinel 480 A 480. includes outlet and handle.	NEMA 4	A36 steel / Polyester	N/A	198.41 lbs	42" X 30" X 12"

Note: Stainless steel cabinet, receptacles and outlets of your choice are available upon request.
If you have any questions, please contact our sales department at **(871) 731 89 41**.